

No.8 | Anchor Bolt [Charge]

Exhibitor's Manual Page 28-29

To: HIROMEYA CO., LTD.

$\overline{}$				
1:	а.	т	Δ	•
_,	u.	Ľ	$\overline{}$	٠

Exhibitor:			Booth No.	
Contact: Mr./Ms. Section:			Management Office Use	
TEL:	FAX:	E-m	E-mail:	
M/				

We will use	1 Yes	2 No
anchor bolts.	1. 165	2. No


Please fill in the floor construction plan and the constructor's name. The exhibitor must observe all the rules and regulations and is responsible for restoring the hall space to its original state.

Туре	Holl-in-anchor		
Number of Anchors	Diameter: m/m Φ Number of anchors: × @¥1,650		
Work will be carried out on	Novemberto		 Please pay a implanting fee (floor recovery cooperation fee) of ¥1,650 per anchor. If the floor is not fully recovered to its original
Restoration work will be carried out on	☐ Sat, Dec. 2	Sun, Dec. 3	state after the exhibition is concluded, a recovery fee of ¥11,000 per anchor applies.
Restoration Method	Cutting by sander only. (Driving into the floor with hammer and cutting using gas burners are not permitted.)		
Attached Document	Booth design drawings (indicating desired positions for implanting hole-in-anchors): 2 copies		
	Company Name:	Contact Person:	
Contractor	Address:	TEL:	
Send an invoice to	☐ 1. Exhibitor	2. Contractor	


Cautions on Implant

- (a) The floor structure is shown below. Bolts of the holed anchors must be fastened to a depth of 80 mm or less and thickness of 20mm or less.
- (b) Anchor bolts may not be implanted on the lids of floor pit, within 20 cm of the pit edges and inside of the pit.
- (c) The use of chemical anchors is prohibited.

<Cross-section drawing>



<Floor Plan Drawing>



Submit to

HIROMEYA CO., LTD. (Mr. Igata)

1-6-1 Ginza, Chuo-Ku, Tokyo 104-0061, JAPAN

TEL: +81-3-3563-0018 FAX: +81-3-3563-0023 E-mail: ipf-en@hiromeya.co.jp